

Uncontrolled document as of January 11, 2009. Refer to website for up to date specifications.

LIGHTS
2460
 StealthLite Rechargeable
 Recoil LED



StealthLite™ Rechargeable 2460 Recoil LED™ Flashlight


The rechargeable version of the [StealthLite 2410 Recoil LED Flashlight](#). The 2460 uses a long-life NiMH battery pack for extended burn time. It comes with a charger base unit that can be installed at home or work using the 110V transformer. Or in a vehicle through direct wiring or 12V plug-in.

Minimum Pack 1 ea.
 Packaged Weight: 1.4 lbs.



StealthLite™ Rechargeable 2460 Recoil LED™ Flashlight Configurations

Cat. #	Description
2460	StealthLite™ Rechargeable 2460 Recoil LED™ Flashlight (Carded)



StealthLite™ Rechargeable 2460 Recoil LED™ Flashlight Specifications

Light Source	Tested Lumen Value	Tested Lux Value (@ 1 meter)
Recoil LED	28.0	3,800
Batteries	Battery Burn Time	Battery Pack/Charging Time
4 AA NiMH (Included)	32 hrs.	NiMH Battery Pack 2-3 hrs.
Watts	Voltage	
1	6	
Length	Weight w/Batteries	Weight w/o Batteries
7" (17.8 cm)	7.8 oz. (0.22 kg)	4.4 oz. (0.12 kg)

StealthLite™ Rechargeable 2460 Recoil LED™ Flashlight Approvals



Class I, Div. 2, Gp. ABCD T4A; Class II, Div. 2 Gp. FG

StealthLite™ Rechargeable 2460 Recoil LED™ Flashlight Accessories

Cat. #	Description
2407	Cordura® Holster
700	Helmet Light Holder
710	Helmet Light Holder

711	Helmet Light Holder
712	Helmet Light Holder
750	Helmet Light Holder
760	Helmet Light Holder
770	Universal Helmet Light Holder
2469	NiMH Replacement Battery Pack
6061F	Direct Wiring Rig for Fast Charger
2455N	12 V Plug-in for Charger
2470F	Desk/Dash Smart Charger Base Unit