

Uncontrolled document as of January 11, 2009. Refer to website for up to date specifications.

**LIGHTS**  
**2480 ELS**  
 Emergency  
 Lighting Station



**2480 Emergency Lighting Station**

Finding dependable lighting in a blackout situation is no longer a problem. The 2480 ELS houses our [MityLite 2440PLB Flashlight](#) (with a photoluminescent body that emits a bright glow in the dark). Use the bright 5-LED array to light your way to safety, powered by alkaline/titanium cells that provide extended burn time and long shelf life. The strong polycarbonate case, with photoluminescent labels that are visible from a long distance, can be mounted on any surface.

Minimum Pack 1 ea.  
 Packaged Weight: 1.5 lbs.

**2480 Emergency Lighting Station Configurations**

Cat. #	Description
2480	2480 Emergency Lighting Station (Boxed)
2440PLB	MityLite™ 2440 LED Flashlight Photoluminescent Body

**2480 Emergency Lighting Station Specifications**

Light Source	Tested Lumen Value	Tested Lux Value (@ 1 meter)
LED	33.0	

Batteries	Battery Burn Time	Battery Pack/Charging Time
4 AA Energizer® e <sup>2</sup> Alkaline (Included)	90 hrs.	N/A

Watts	Voltage
1.1	6

Length	Weight w/Batteries	Weight w/o Batteries
6.5" (16.5 cm)	6.24 oz. (0.18 kg)	

**2480 Emergency Lighting Station Approvals**



Class I, Div. 2; GP.ABCD Max. Surface Temp. 116° C