

Uncontrolled document as of January 11, 2009. Refer to website for up to date specifications.

LIGHTS
3600
 Little Ed




Little Ed™ 3600 Flashlight

Don't be fooled by the name. This right angle light packs a punch. The 3600 Flashlight is made of ABS resin that's extremely strong, light weight, corrosion proof, and resistant to extreme temperatures. The super bright Xenon beam cuts through thick smoke and dust and the one-handed switch is easy to operate, even with gloves. For hands-free use, a stainless steel clip is built in. Attach the Little Ed to your turnout coat or work shirt. It is powered by 4 AA alkaline cells (included).

Minimum Pack 1 ea.
Packaged Weight: 11.7 oz.

Little Ed™ 3600 Flashlight Configurations

Cat. #	Description
3600	Little Ed™ 3600 Flashlight (Carded)
3600PL	Little Ed™ 3600 Flashlight w/ Photoluminescent Shroud



Little Ed™ 3600 Flashlight Specifications

Light Source	Tested Lumen Value	Tested Lux Value (@ 1 meter)
Xenon	25.0	5,800
Batteries	Battery Burn Time	Battery Pack/Charging Time
4 AA Alkaline (Included)	4 hrs.	N/A
Watts	Voltage	
3.2	6	
Length	Weight w/Batteries	Weight w/o Batteries
7.51" (19.1 cm)	10.1 oz. (0.29 kg)	6.6 oz. (0.19 kg)

Little Ed™ 3600 Flashlight Approvals



Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G -35° TO +40°C.



Class I, Div. 2, Groups A,B,C,D, T4



Class I, Div. 1,Gp.D, Class I, Zone 1 GP. IIA Temp.Class T3 Energizer E91 Only Conforms to STD. UL 783

Little Ed™ 3600 Flashlight Accessories

Cat. #	Description
2404	Little Ed™ 3600 Lamp Module

